

PRODUCT DATA SHEET

SikaGrind®-401 KE

GRINDING AID AND QUALITY IMPROVER FOR THE PRODUCTION OF CEMENT

DESCRIPTION

SikaGrind®-401 KE is a chloride free liquid additive to allow easier grinding of cement and enhance the quality of all types of cement. SikaGrind®-401 KE has been specifically developed to obtain cements without brown or yellow discolorations.

USES

- Increase the production rate of cement
- Improve the efficiency of the mill and separator
- Enhance the quality of the cement

CHARACTERISTICS / ADVANTAGES

SikaGrind®-401 KE provides the following advantages in the cement production:

- Increased production rate
- Easier achievement of the desired cement fineness
- Cost savings due to lower specific power consumption per ton

SikaGrind®-401 KE provides the following advantages to the finished cement:

- Increased early strength
- Improved powder flow characteristics

PRODUCT INFORMATION

Composition	Blend of amines and glycols
Packaging	<ul style="list-style-type: none"> ▪ 1000 kg IBC ▪ Bulk Tanker
Appearance / Colour	Clear liquid
Shelf life	At least 12 months shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging.
Storage conditions	Stored at temperatures between +5°C and +35°C. Protect from frost, direct sunlight and contamination. Note: When delivered in bulk, the tanks and equipment used must be free from contaminants
Density	1.03 ± 0.02 kg/l (at +25°C)
pH-Value	3.00 ± 1.00 (at +25°C)

APPLICATION INFORMATION

Recommended dosage	Typical dosage rates of SikaGrind®-401 KE are between 0.3 - 0.6 kg per ton of cement (0.03% - 0.06% of total weight = cement clinker + additions). The optimum dosage to achieve the desired characteristics shall be determined in plant trials. Influencing factors are e.g. the properties of clinker, type of cement and other plant variables. For consistent results, SikaGrind®-401 KE must be accurately dispensed.
---------------------------	---

Compatibility

Cements treated with SikaGrind®-401 KE are compatible in concretes produced with all commercial admixtures including air entrainers, water reducers, retarders and superplasticizers. The performance of concrete admixtures are not adversely affected by the use of SikaGrind®-401 KE.

Dispensing

SikaGrind®-401 KE is added onto the clinker feed shortly before the mill entrance or directly into the grinding mill. Suitable dosage pumps with adjustable flow rates shall be used for accurate dosing. Note: Periodically, the end of the additive tube/hose shall be checked to ensure that it is not blocked!

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safetyrelated data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kenya Limited

Josh Industrial Estate
P.O Box 38645 · 00623 Nairobi · Kenya
Mobile: +254 711 140234 / +254 786
140234
Web: ken.sika.com

Product Data Sheet

SikaGrind®-401 KE
June 2026, Version 01.01
021407011000246820

SikaGrind-401KE-en-KE-(06-2026)-1-1.pdf