

PRODUCT DATA SHEET

Sika® Aggregate-508

Component C for use with Sikafloor®-264 coating systems.

DESCRIPTION

A selection of carefully graded, kiln dried and blended natural aggregates.

USES

Sika® Aggregate-508 is used as the Component C aggregate for Sikafloor®-264.

CHARACTERISTICS / ADVANTAGES

Specifically graded and blended for use with Sikafloor®-264 floor coating systems.

PRODUCT INFORMATION

Packaging	20 kg bags
Shelf life	Twenty-four (24) months from date of production if stored correctly in unopened, undamaged and original sealed packaging.
Storage conditions	Store in dry and cool conditions. Protect from moisture.
Maximum grain size	Aggregate Grading: 0.1 - 0.3 mm
Bulk density	~ 1.55 kg/litre (dry)

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Refer to the specific Sikafloor® MultiDur system data sheet for full information.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kenya Limited

Josh Industrial Estate
P.O Box 38645 · 00623 Nairobi · Kenya
Mobile: +254 711 140234 / +254 786
140234
Web: ken.sika.com

Product Data Sheet

Sika® Aggregate-508
October 2025, Version 01.01
020816010010000075

SikaAggregate-508-en-KE-(10-2025)-1-1.pdf