

PRODUCT DATA SHEET

SikaRoof® Cleaner L-100

Sikaplan Cleaner

DESCRIPTION

SikaRoof® Cleaner L-100 is a solvented cleaner for preparing Sikaplan® roof waterproofing membranes

USES

- Cleaner to remove local contamination from Sikaplan roof waterproofing
- Preparation of old Sikaplan® PVC membranes for welding applications
- Diluent for SikaRoof® Adhesive C-733
- Degreasing metal sheets

CHARACTERISTICS / ADVANTAGES

- Dissolves contamination from adhesive resin, mastic and bitumen
- Evaporates quickly
- The cleaner may be suitable to clean metal equipment and tools

PRODUCT INFORMATION

Composition	Mixture of high volatile solvents				
Packaging	<table border="0"> <tr> <td>Container:</td> <td>4.5 L (4kg)</td> </tr> <tr> <td>Packing unit:</td> <td>Euro pallet or single container</td> </tr> </table> <p>Refer to current price list for packaging variations.</p>	Container:	4.5 L (4kg)	Packing unit:	Euro pallet or single container
Container:	4.5 L (4kg)				
Packing unit:	Euro pallet or single container				
Appearance / Colour	Liquid / Transparent				
Shelf life	24 months from date of production				
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions and protected from direct sunshine. The product is highly flammable: Safety regulations regarding storage and handling of dangerous goods must be observed. Always refer to packaging.				
Density	0,9 kg/l				

APPLICATION INFORMATION

Ambient air temperature	+30 °C min. / +60 °C max.
Substrate temperature	-20 °C min. / +60 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

Application as cleaner SikaRoof® Cleaner L-100 has high deteriorating effect on textile colours and dirt. In order to prevent discolorations on the membrane surface, it is recommended to use white cleaning cloths. Spilt SikaRoof® Cleaner L-100 must be soaked up with dry cloths immediately. Cleaner on the membrane surface must be fully evaporated prior to seam welding.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kenya Limited

Josh Industrial Estate
P.O Box 38645 · 00623 Nairobi · Kenya
Mobile: +254 711 140234 / +254 786
140234
Web: ken.sika.com

Product Data Sheet
SikaRoof® Cleaner L-100
September 2025, Version 02.01
02094507105000007

SikaRoofCleanerL-100-en-KE-(09-2025)-2-1.pdf