

## PRODUCT DATA SHEET

# Sika® Antisol®-107

(formerly MKure 107)

Water based concrete curing compound, white pigmented for solar reflectance

### DESCRIPTION

**Sika® Antisol®-107** incorporates a white pigment which at recommended coverage rates gives a day-light reflectance value of 60-80%. This permits a high curing efficiency to be maintained even in conditions of intense ambient light.

**Sika® Antisol®-107** is a solvent free, membrane forming wax emulsion, suitable for spray application to freshly poured concrete.

The resultant film retains sufficient moisture in the concrete to ensure full hydration of the cement, essential for optimum strength development. Membrane cured concrete is typically harder and exhibits a dust free surface with a reduced incidence of drying shrinkage cracks.

### USES

As a more effective and economical alternative to hessian and water and polythene curing regimes. Suitable for use on all concrete surfaces.

### CHARACTERISTICS / ADVANTAGES

- Eliminates the need for water.
- Single application.
- Promotes a harder dust free surface.
- Cured film is clear and water repellent.
- Reduces drying shrinkage.
- High curing efficiency.
- Reduced labour costs.
- Water based.
- Solar reflective.

### APPROVALS / CERTIFICATES

ASTM C309 Type 2 Class A

Water retention (ASTM C309) - Pass

Drying time (ASTM C309) - 3 hours

### PRODUCT INFORMATION

<b>Packaging</b>	Sika® Antisol®-107 is available in 20 litre or 210 litre drums.
<b>Appearance / Colour</b>	White liquid Finish appearance - White solar reflective, tack free, water repellent
<b>Shelf life</b>	12 months when stored correctly and in an unopened container.
<b>Storage conditions</b>	Store under cover, out of direct sunlight and protect from extremes of temperature.  Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult the Sika Technical Services Department.

Density 0.970 -1.010

pH-Value 7.0 – 10.0

## APPLICATION INFORMATION

### Dispensing

#### DIRECTIONS FOR USE

The compound should be spray applied as evenly as possible on to the freshly placed concrete.

For horizontal surfaces Sika® Antisol®-107 should be applied as soon as the initial surface sheen has disappeared from the concrete surface. In the case of formed concrete, the Sika® Antisol®-107 should be applied immediately on removal of the formwork. To assist breakdown of the Sika® Antisol®-107 film on vertical and formed surfaces, it is essential to dampen down the concrete with clean water prior to application.

### Consumption

#### COVERAGE

The recommended rate of application is **5-6 square metres per litre**. This corresponds to that at which Sika® Antisol®-107 has been tested, and at which it attains the claimed degree of curing efficiency. In favourable conditions such as shaded interior surfaces, adequate curing can be achieved with extended coverage rates.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER INFORMATION

### FILM BREAKER

The time for deterioration of the membrane is dependent on a number of variables, which include film thickness, degree of exposure to weathering, traffic, UV light, and the porosity of the substrate concrete.

### SUBSEQUENT SURFACE FINISHES

It is important that the complete removal of the Sika® Antisol®-107 should be ensured prior to the application of any surface finish or additional treatment. It is recommended that where the concrete is to receive a coating or the application of tiles, the use of Sika Antisol-181 is considered.

Sika Antisol-181 is a resin based non-degrading curing membrane meeting the requirements of ASTM C-309 Type 1 Class B. It is additionally formulated to act as a primer for many finishes or to seal concrete surfaces and provide a degree of abrasion to flatwork.

## ECOLOGY, HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation. Consult the Safety Data Sheet (SDS) for detailed information.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### **Sika Kenya Limited**

Mudher Industrial Complex, Mombasa  
Road  
P.O Box 38645 - 00623 Nairobi, Kenya  
Mobile: +254 711 140234 / +254 786  
140234  
Web: ken.sika.com

### **Product Data Sheet**

Sika® Antisol®-107  
October 2024, Version 02.01  
02140500000002044

SikaAntisol-107-en-KE-(10-2024)-2-1.pdf

